



NUTRUNNERS

HP 0,6 KW 0,44

Series 72/90



Performances and dimensions

Model	Free speed r/min	Speed at max power r/min	Torque at max power Nm	Starting torque Nm	Torque Nm	Quote "L" mm	Weight Kg.	Air consum l/sec.
M72/90PT05	18	9	413	420	560	282	5,4	8,5
P72/90PT05	18	9	413	420	560	262	5,4	8,5
M72/90N434	15	7	505	520	680	299	6,2	8,5
P72/90N434	15	7	505	520	680	295	6,2	8,5
M72/90NT34	11	5	685	700	930	299	6,2	8,5
P72/90NT34	11	5	685	700	930	295	6,2	8,5
M72/90P434	8	4	890	900	1200	299	6,2	8,5
P72/90P434	8	4	890	900	1200	295	6,2	8,5
M72/90PT34	6	3	1165	1200	1600	299	6,2	8,5
P72/90PT34	6	3	1165	1200	1600	295	6,2	8,5



ATTENTION

All data are based on a working pressure of 7 bar

Lubrication:

2-3 drops/1' continuous operation

4-6 drops/1' intermittent operation

Filtration:

Use 64 μ filtration or better

Axial load:

Not admitted

Operative temperature:

da-20° a +80°

